



SMART
One™

MATRIX-BBO BACnet ROUTER



The Matrix-BBO is a BTL-listed MS/TP to IP compliant network router, providing users with connectivity to SmartOne devices over IP local networks, wide area networks, and even the Internet when properly configured. The device has one on-board RS-485 port that is configurable and capable of hosting up to 64 SmartOne™ devices. This router also provides support for all standard BACnet baud rates, routing to BACnet/IP or BACnet/Ethernet, and can even act as a BBMD and Foreign Device registrar. Using any standard web browser to access the device, setup and configuration can be accomplished through entering the product's password protected web-server.

FEATURES

- Connects BACnet networks running over different datalink layers
- Full Annex J support including BBMD and foreign device registration
- Intuitive web browser-based configuration
- One (1) 10/100 Base-T Ethernet port
- One (1) EIA-485 port
- SmartOne devices can be programmed with SmartOne Configuration Wizard over IP through this device


NETWORKING

- The Matrix-BBO Router communicates between BACnet MS/TP devices on the EIA-485 network and devices on a BACnet/IP or BACnet/Ethernet network.
- Line signaling: EIA-485, optically isolated,
- Wiring: shielded, twisted pair (EIA-485); CAT5 (Ethernet)
- Network protection: PTC, Tranzorb (EIA-485)
- Communications speed (EIA-485): 9600, 19.2k, 38.4k, 57.6k, 76.8k, 115.2k baud
- Network configuration: multi-drop bus
- Protocols: BACnet/IP, BACnet MS/TP, BACnet/Ethernet



BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to requirements of ASHRAE Standard 135 is the responsibility of the BACnet International. BTL is a registered trademark of the BACnet International.

SYSTEM ARCHITECTURE



Note: To interface with SmartOne devices users must utilize either a Matrix-BBO or other Bacnet IP routing device (sold separately) or use the SMT-Link and DB-25 bundle (sold separately)

SPECIFICATIONS

Terminations	Dimensions	Processor
One (1) EIA-485 port One (1) RJ-45 Ethernet port	Overall size: 14 x 11 x 3.5" (35.6 x 27.9 x 8.9 cm) Weight: 5.0 lbs (2.26 Kg)	High-Speed 32-bit processor built on ARM Technology

Input Supply	Operating Environment	Agency Listings
12-29 VDC/VAC, 50/60 Hz, Nominal 2.7A maximum	• Operating Temperature: 32° to 122° F (0° to 50° C) • Relative Humidity: 0 to 80% RH, non-condensing	• UL listed 916, Management Equipment, Energy (PAZX) • FCC rules Part 15 Class B computing Device • UL Recognized 873, Temperature Indicating and Regulating Equipment (XAPX; XAPX7) • Complies with CE directives and standards • BTL Listed as B-Other

American Auto-Matrix is a Service-Disabled Veteran-Owned Small Business / Woman-Owned Business (CCR Cage #4LL80)

One Technology Lane Export, Pennsylvania 15632-8903 U.S.A Tel (1) 877-AAM-HVAC Fax (1) 724-327-6124

Email: aam@aamatrix.com On the Web: www.aamatrix.com



This document must not be used or copied in part or in whole for any purpose other than that for which it was intended. This document does not constitute any warranty, expressed or implied. Every effort has been made to ensure that all information was correct at the time of publication. American Auto-Matrix reserves the right to alter the specifications, performance, capabilities, and presentation of this product at any time. American Auto-Matrix, Smart Building Solutions, and SmartOne are registered trademarks of American Auto-Matrix. BACnet® is a registered trademark of ASHRAE. © 2011 American Auto-Matrix.

www.bacnetcontrol.com